

## **Anti-Tack Reference Guide**

| PRODUCT                |        |  | FEATURES      |                                |             |      |             |             |   |             |             |             |             |                      |                     |              |
|------------------------|--------|--|---------------|--------------------------------|-------------|------|-------------|-------------|---|-------------|-------------|-------------|-------------|----------------------|---------------------|--------------|
|                        |        |  | % Usage Level | Crystalline Silica,<br>% by wt | CaSt        | MgSt | ZnSt        | Pickup Rate | Uniform Coating   | Fast Drying | Low Foaming | Low Dusting | No Flaking  | Low Settling<br>Rate | Improved<br>Wetting | Matte Finish |
| DISPERSIBLE<br>POWDERS | Slab   | CALFORD® R-268<br>Highest Performance Grade                              | 1.6-2.2       | <1                             | -           | ~    | -           | <0.07       | ~   | <b>~</b>    | ~           | ~           | ~           | ~                    | <b>&gt;</b>         | <b>~</b>     |
|                        |        | CALFORD® R-251C<br>No talc, mica, kaolin clay<br>(hard or soft), or zinc | 1.8-2.8       | <1                             | >           | -    | -           | <0.07       | ~   | <b>*</b>    | ~           | ~           | •           | ~                    | <b>&gt;</b>         | <b>&gt;</b>  |
|                        |        | CALFORD® R-341<br>Low Cost /<br>High Performance Grade                   | 1.6-2.2       | <1                             | >           | _    | -           | <0.07       | ~   | •           | ~           | ~           | •           | ~                    | >                   | <b>~</b>     |
|                        | Pellet | RUBBERCOTE 262   | 7-10          | <1                             | <b>&gt;</b> | -    | -           | _           | ~   | •           | •           | •           | ~           | •                    | <b>~</b>            | V            |
|                        |        | RUBBERCOTE 430   | 4.5-6         | <2.5                           | >           | -    | -1          | -           | -   | -1          | -           | -           | <b>&gt;</b> | -                    | 1                   | <b>~</b>     |
| SLURRY                 |        | CALFORD® S-384<br>31% Solids Dispersion                                  | 2-4           | <1                             | <b>&gt;</b> | _    | -           | <0.07       | ~   | <b>~</b>    | ~           | ~           | ~           | ~                    | <b>&gt;</b>         | <b>~</b>     |
| SOAPS                  |        | K-LUBE®  | 10            | N/A                            | ı           | -    | -           | -           | Rubber Release Agent / Banbury Chute Lubricant –<br>Imparts a Clear Coating on Rubber (20% Liquid Potassium Soap) |             |             |             |             |                      |                     |              |
|                        |        | RELEASE 44   | 6-20          | N/A                            | _           | _    | _           | _           | Rubber Release Agent / Mold & Mandrel Release –<br>Imparts a Clear Coating on Rubber (40% Liquid Potassium Soap)  |             |             |             |             |                      |                     |              |
|                        |        | RL 10 OSAF   | 6-20          | N/A                            | ı           | -    | -           | _           | Rubber Release Agent / Mold & Mandrel Release –<br>Imparts a Clear Coating on Rubber (33% Liquid Potassium Soap)  |             |             |             |             |                      |                     |              |
| ZINC                   |        | ZINC STEARATE 161  | 3-5           | N/A                            | ı           | _    | ~           | -           | Zinc Stearate Powder for creating a wettable dispersion.  |             |             |             |             |                      |                     |              |
|                        |        | ZINC STEARATE 201  | 100           | N/A                            | 1           | -    | <b>~</b>    | _           | Zinc Stearate Powder for Dusting Operations and Floating on Bath Systems.   |             |             |             |             |                      |                     |              |
|                        |        | CALFORD® R-236-1   | 3-10          | N/A                            | _           | _    | <b>&gt;</b> | _           | Fast Drying Zinc Paste. Ideal for water-cooled batch off. (25% Solids)  |             |             |             |             |                      |                     |              |

PLEASE NOTE: The purpose of this data is to provide general information and advice. All statements, formulations and recommendations are offered in good faith but without guarantee. Users of Blachford products are themselves responsible for compliance with any legal provisions including those relating to patent laws and accident prevention. CALFORD and K-Lube are registered trademarks of H.L. Blachford Ltd.

